

T100 Series/T50 Voltage and Continuity Testers

FLUKE®



Fluke T140



Fluke T120



Fluke T100



Fluke T50



The fast and easy solution to voltage, continuity and phase rotation testing

Fluke T50

Offers a low cost solution to voltage-continuity measurement. It contains an acoustic and optic continuity test and features a single pole test for phase detection.

Fluke T100 Series

The fast and easy solution to voltage, continuity and resistance measurements. Ideal for site conditions, the 3 models of the T100 Series 2-pole testers have a rugged construction and ergonomically formed housing for perfect handling. All models offer a patented three-phase

rotation detection system providing quick phase rotation indication. Moreover they have a special electrical torch function for working in low light level environments and have an ingress protection rating of IP65. The T100 Series are compliant with EN 61010-1 and EN61243-3 requirements.

Features

	T50	T100	T120	T140
Display			LCD	LCD
Led Bargraph	10 LED's	12 LED's	12 LED's	12 LED's
Backlight				●
Resistance measurement				●
Switchable load				●
Voltage test	●	●	●	●
Optical and acoustical continuity test	●	●	●	●
Rotary field indication		●	●	●
Single pole test for phase detection	●	●	●	●
Indication of polarity	●	●	●	●
Electrical torch function		●	●	●
Probe tip protection		●	●	●
The voltage display also functions when using discharged - or o batteries	●	●	●	●

Specifications

	T50	T100	T120	T140
Voltage AC/DC	12 - 690 V	12 - 690 V	12 - 690 V	12 - 690 V
Continuity	0 - 200 kΩ	0 - 400 kΩ	0 - 400 kΩ	0 - 400 kΩ
Frequency	0 - 65 Hz	0 - 400 Hz	0 - 400 Hz	0 - 400 Hz
Phase rotation	-	100 to 690 V	100 to 690 V	100 to 690 V
Resistance measurement	-	-	-	Up to 1999 Ω
Response time	< 0.1 s	< 0.1 s	< 0.1 s	< 0.1 s

Included Accessories

Two 1.5V batteries and instruction sheet

Ordering Information

Fluke T50 Voltage/Continuity Tester
 Fluke T100 Voltage/Continuity Tester
 Fluke T120 Voltage/Continuity Tester
 Fluke T140 Voltage/Continuity Tester

UK versions are compliant with GS38

Size T50 (HxWxD): 210 mm x 40 mm x 22 mm

Size T100/T120/T140 (HxWxD):

240 mm x 56 mm x 24 mm

Case: T100/T120/T140: IP65
 (water-jet and dust tight protection)
 T50: IP54

Weight T50: 130 g

Weight T100/T120/T140: 180 g

Two year warranty

Recommended Accessories



C23 (T50)



C33 (T100 Series)